



Ceiling Void & Soffit Spraying

Colour+fast (SC-01) Soffit Coating

Specification & Datasheet

Description

Colour+fast (SC-01) Soffit Coating is a high performance, self priming paint system, specifically formulated for the on site spray coating of ceiling soffits and ceiling voids.

Extensively used in the refurbishment of supermarkets, warehouses and offices, this spray applied paint system provides excellent adhesion to both concrete and metal surfaces, allowing for rapid decoration of the ceiling soffits, steel work and associated services.

Formulated specifically for spray application, this professional quality, high opacity paint system is water based and quick drying, providing a hard wearing and durable finish.

Spray applied in-situ, following extensive masking and protection of adjacent surfaces. Colour+fast (SC-01) provides the market leading ceiling soffit refurbishment solution.

Specification

Coating:

colour+fast (SC-01) Soffit Coating

Surface:

Concrete Soffits, Metal Soffits, Steel work and Services

Colour:

Brilliant White Matt (BS 00 E 55) as standard
Full range of BS and RAL Colours available

Preparation:

1. Remove all loose and flaking paint back to a hard edge and feather back.
2. Remove all dirt and carbon deposits.
3. Fully mask and protect all adjacent surfaces that are not to be sprayed, to ensure that walls, floors, furniture and stock are protected.

4. Fully mask and protect all fixtures within the soffit that are not to be sprayed, to ensure that sprinkler heads, speakers, smoke detectors etc. are protected.

Application:

1. Spray apply 1 no. full coat of colour+fast (SC-01) to existing ceiling soffit, steelwork and services by airless spray to achieve a uniform appearance and finish.

2. De-mask and clean down.

Applicator:

colour+fast™ (SC-01) coating to be applied by approved applicator



Key Properties

- Self Priming
- Excellent Adhesion
- Durable Finish
- Water Based
- Low Odour
- High Opacity
- Rapid Drying
- BS & RAL Colours
- Matt Finish



Colour+fast™ Soffit Coating

Datasheet

Recommended Uses

Refurbishment of supermarkets, warehouses, factories and commercial offices.

Type of substrate

Internal concrete and metal soffits, including steelwork, ductwork, cable trays and associated services.

Colour Range

Standard colour is Brilliant White (BS 00 E 55). Full range of BS and RAL Colours available.

Finish

Matt

Volume Solid

23%

Coverage

Approximately 5-6 square metres per litre, depending on the nature and porosity of the surface.

Drying Time

Touch dry in 1-2 hours.
Re-coatable after 2-4 hours.

Transportation & Storage

To avoid risk of spillage, always store and transport in a secure upright position. Protect from frost.

Thinner

Clean Water.

VOC Content

Low VOC content 0.3-7.99%. VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

Film Thickness

Wet: 90 µm, Dry: 21 µm

Preparation

Remove all peeling, flaking and poorly adhered coatings back to a hard edge and feather back. Clean surfaces of all dirt and carbon deposits and apply a mordant solution to any new galvanised surfaces.

Masking & Protection

Fully mask and protect all adjacent surfaces that are not to be sprayed, to ensure that walls, floors, furniture and stock are protected. Mask and protect all fixtures within the soffit that are not to be sprayed, to ensure that sprinkler heads, speakers, smoke detectors etc. are protected.

Application

Stir well. Application by airless spraying equipment to ensure a uniform appearance and finish. Do not apply in temperatures below 10C.

Cleaning

Clean equipment immediately after use with warm soapy water and rinse thoroughly.

Precautions

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

Sizes

10 Litre, 15 Litre

Supply Information

Approved Applicators

Application must only be undertaken by approved and experienced operatives.

Customer Service

Free site survey reports, quotations and technical advice are available from sprayzone.

Project Management

Each project is directly controlled by sprayzone's experienced and qualified contracts department.

References

Current references can be obtained by contacting sprayzone. Case Studies also available at our website: www.sprayzone.co.uk

Other Services

Sprayzone have developed coating systems for suspended ceilings, shopfronts, windows, cladding panels and walls. Data sheets for these systems are available on request.

